

Industry Standard, Flexible Architecture

OPEN



GREEN

Less Heat, Less Power Consumption

STABLE

Robust Design, Quality Parts

Stable and
Reliable Solution

Server/Workstation

Motherboard

2U24E-EGS2

User Manual

English



Version 1.0

Published July 2023

Copyright©2023 ASRock Rack Inc. All rights reserved.

Copyright Notice:

No part of this documentation may be reproduced, transcribed, transmitted, or translated in any language, in any form or by any means, except duplication of documentation by the purchaser for backup purpose, without written consent of ASRock Rack Inc.

Products and corporate names appearing in this documentation may or may not be registered trademarks or copyrights of their respective companies, and are used only for identification or explanation and to the owners' benefit, without intent to infringe.

Disclaimer:

Specifications and information contained in this documentation are furnished for informational use only and subject to change without notice, and should not be construed as a commitment by ASRock Rack. ASRock Rack assumes no responsibility for any errors or omissions that may appear in this documentation.

With respect to the contents of this documentation, ASRock Rack does not provide warranty of any kind, either expressed or implied, including but not limited to the implied warranties or conditions of merchantability or fitness for a particular purpose.

In no event shall ASRock Rack, its directors, officers, employees, or agents be liable for any indirect, special, incidental, or consequential damages (including damages for loss of profits, loss of business, loss of data, interruption of business and the like), even if ASRock Rack has been advised of the possibility of such damages arising from any defect or error in the documentation or product.



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

CALIFORNIA, USA ONLY

The Lithium battery adopted on this motherboard contains Perchlorate, a toxic substance controlled in Perchlorate Best Management Practices (BMP) regulations passed by the California Legislature. When you discard the Lithium battery in California, USA, please follow the related regulations in advance.

“Perchlorate Material-special handling may apply, see www.dtsc.ca.gov/hazardouswaste/perchlorate”

ASRock Rack’s Website: www.ASRockRack.com

Setting up the Server in a Restricted Access Location/Restricted Access Area

- Access can only be gained by service persons or by users who have been instructed about the reasons for the restrictions applied to the location and about any precautions that shall be taken.
- Access is through the use of a tool or lock and key, or other means of security, and is controlled by the authority responsible for the location.
- Leave enough clearance (25 inches in the front and 30 inches in the back of the rack) to allow the front door to be opened completely and to allow for sufficient airflow.
- This product is for installation merely in a Restricted Access Location.
- This product is not suitable for use with visual display work place devices according to §2 of the the German Ordinance for Work with Visual Display Units.
- Only skilled person and Instructed person can remove the chassis covers to access the inside of the system.

Replaceable Batteries

CAUTION

RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE.

DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS

Warning

When removal of the chassis lid required for servicing:

- Turn off power and unplug any power cords/cables, and
- Reinstall the chassis lid before restoring power.



Important Safety Instructions

Pay close attention to the following safety instructions before performing any of the operation. Basic safety precautions should be followed to protect yourself from harm and the product from damage:

- Operation of the product should be carried out by suitably trained, qualified, and certified personnel only to avoid risk of injury from electrical shock or energy hazard.
- Disconnect the power cord from the wall outlet when installing or removing main system components, such as the motherboard and power supply unit.
- Place the system on a stable and flat surface.
- Use extreme caution when working with high-voltage components.
- When handling parts, use a grounded wrist strap designed to prevent static discharge.
- Keep the area around the system clean and clutter-free.
- Keep all components and printed circuit boards (PCBs) in their antistatic bags when not in use.
- Handle a board by its edges only; do not touch its components, peripheral chips, memory modules or contacts.
- The power cord must be connected to a socket or outlet with a ground connection.

Contents

Chapter 1 Introduction	1
1.1 Shipping Box Contents	2
1.2 Specifications	3
Chapter 2 Server System Overview	4
2.1 System Components	4
2.2 Internal Features	5
2.3 System Front Panel	7
2.4 System Rear Panel	7
2.5 Front Control Panel Buttons and LEDs	8
2.6 Drive Tray LEDs	10
2.7 PSU LED	12
Chapter 3 Hardware Installation and Maintenance	13
3.1 Server Top Cover	14
3.2 Hard Drive	16
3.3 System Fan	19
3.4 Power Supply	20
3.5 Add-in Card	21

Chapter 1 Introduction

Thank you for purchasing 2U24E-EGS2, a reliable barebone system produced under ASRock Rack's consistently stringent quality control. It delivers excellent performance with robust design conforming to ASRock Rack's commitment to quality and endurance.

This guide provides the instructions of insertion and extraction of chassis components, such as chassis covers, system fans, power supplies, hard disk drive trays, and other main components this system supports. If the system is pre-installed a serverboard, please refer to the user's manual of the serverboard for the information of the serverboard components, specifications and BIOS settings.

System	ASRock Rack Server Board
2U24E-EGS2	SP2C741D32TM3



Because the hardware specifications might be updated, the content of this documentation will be subject to change without notice.



The illustrations shown in this manual are for reference purposes only and may not exactly match the model purchased.



*If requiring technical support related to this system, please visit the website for specific information about the using model.
<http://www.asrockrack.com/support/>*

1.1 Shipping Box Contents

Item	Quantity
2U24E-EGS2 (2U Barebone)	1
System Board (MB)*	1
Power Supply Unit*	2
System Fan*	6
HDD Backplane (BPB)*	4
Front Panel Board (FPB)*	2
Riser cable*	2
Accessory Box	1
1U Cooler/Heatsink	2
Slide Rail	1

* The components are pre-installed.



If any items are missing or appear damaged, contact the authorized dealer.

1.2 Specifications

2U24E-EGS2	
System Physical Status	
Form Factor	2U Rackmount
Dimension (D x W x H)	800 x 438 x 87.3 mm (31.50" x 17.24" x 3.44")
Support MB	SP2C741D32TM3
Front Panel	
Buttons	<ul style="list-style-type: none"> • Power w/ LED • ID w/ LED • System Reset
LEDs	System Fault
I/O Ports	2 Type-A (USB3.2 Gen1)
External Drive Bay / Storage	
Front Side Drive Bay	24 Hot-swap 2.5" NVMe drive bays
Front Side Backplane	three 8-ports NVME passive backplane
Rear Side	2 Hot-swap 2.5" SATA drive bays
Rear Side Backplane	one 2-ports SATA backplane
Internal	2 M-key (PCIe4.0 x4), support 22110/2280 form factor
System Fan	
Fan	6 PWM fixed 60x56 mm fans
Power Supply	
Type	1+1 CRPS
Output Watts	2700W
Efficiency	80-PLUS Platinum
AC Input	100-240V, 60/50Hz

*Please be noted that the functions are supported depending on the type of the server board.




Please refer to the user manual of the motherboard you use for detailed information about motherboard components and features.

Chapter 2 Server System Overview


This chapter provides diagrams showing the location of important components of the server system.

2.1 System Components



**The illustrations in this User Manual are for references only. The actual product may be slightly different by SKU.*


2.2 Internal Features



No.	From
1	Serverboard
2	Power Supply Units (PSU1)
3	Power Supply Units (PSU2)
4	2 x 2.5" Hot-swap 2.5" SATA drive bays


No.	From
5	System Fan 6
6	System Fan 5
7	System Fan 4
8	System Fan 3
9	System Fan 2
10	System Fan 1
11	2.5" Drive Backplane Board
12	24 x Hot-swap 2.5" NVMe Drive Bays
13	Add-in card 1 x16 (for PCIE slot on the server board)
14	Add-in card 2 x16 (for PCIE slot on the server board)

2.3 System Front Panel




No.	Description
1	2 x USB3.2 Gen1
2	Control Panel (depends on the specification of the server board)
3	24 x Hot-swap 2.5" NVMe Drive Bays

2.4 System Rear Panel



No.	Description
1	2 x Power Supply Units (PSU)
2	Rear Vent
3	I/O Shield (depends on the specification of the server board)
4	2 x Hot-swap 2.5" SATA drive bays
5	2 x Add-in card x16 (for PCIE slot on the server board)
6	2 x OCP 3.0

2.5 Front Control Panel Buttons and LEDs



No.	Description
1	Power Button and LED
2	System Status LED
3	ID Button and LED
4	System Reset Button

**Please be noted that the functions are supported depending on the type of the server board.*

System Reset Button

When the system is completely unresponsive, press the system reset button to reboot the server without shutting it off and initialize the system.

ID Button

Press the ID button to toggle the front panel ID LED and the baseboard ID LED on and off. This allows user to locate the server that working on from behind a rack of servers.

Power Button

Press the power switch button to toggle the system power on and standby/sleep modes. To remove all power from the system completely, disconnect the power cord from the server.

Status LED Definitions

LAN LED	
Status	Description
Blinking Green	Network access
Solid Green	LAN is present
Off	No LAN is present

HDD Status LED	
Status	Description
Blinking Green	HDD access
Off	HDD idle


System Status LED	
Status	Description
Red	System process fault
Off	Running or normal operation

ID LED	
Status	Description
Blue	System identification is active
Off	System identification is disabled

Power LED	
Status	Description
Blue	Power on
Blinking Blue	Standby(Sleep) mode
Off	Power off

2.6 Drive Tray LEDs

3.5" Drive Tray




No.	Description
1	HDD Power LED
2	HDD Activity LED

Status LED Definitions

HDD Power LED	
Status	Description
Solid Blue	HDD powered-on
Off	No power to HDD

HDD Activity LED	
Status	Description
Solid Green	HDD active
Blinking Green	HDD accessing or reading
Solid Red	HDD failed
Off	HDD powered-off

2.5" Drive Tray




No.	Description
1	HDD LED

Status LED Definitions

HDD LED	
Status	Description
Solid Green	HDD active
Blinking Green	HDD accessing or reading
Solid Red	HDD failed
Blinking Red (4Hz)	HDD positioning
Blinking Red (1Hz)	HDD reconnection
Off	HDD powered-off

2.7 PSU LED



PSU Status LED

Status	Description
Green	Normal work; output ON and OK
Amber	Module fault/protection in operating mode (failure, OCP, OVP, Fan Fail, OTP, UVP) AC cord unplugged
Amber blinking at 0.5Hz	Warning (high temp, high power, high current, slow fan)
Green blinking at 0.5Hz	AC Present Only 12VSB on (PS off) or PS in Smart Redundant state

Chapter 3 Hardware Installation and Maintenance

This chapter helps user to assemble the chassis and install components.

Before You Begin

Before working with the server, pay close attention to the “Important Safety Instructions” at the beginning of this manual.

1. Make sure the server is powered off.

Power down the server if it is still running.

(1) Press the Power button to power off the server from full-power mode to standby-power (sleep) mode. The Power LED at the front turns from solid green to blinking green.

(2) Disconnect the power cord first from the AC outlet and then from the server.

The power LED turns off.



The server is not completely powered down when pressing the Power button on the front panel. The Power button lets the server toggle between Power On and Standby (Sleep) modes. Some internal circuitry remain active in the Standby mode. To remove all power from the system completely, be sure to disconnect the power cord from the server.

2. Ensure having a clean and stable working environment. Avoid dust and dirt because contaminants may cause malfunctions.
3. Ground yourself properly before touching any system component. A discharge of static electricity may damage components. Wear a grounded wrist strap if available.

Installing Procedures

The followings are prerequisite to be installed.

- 3.5" or 2.5" HDD(s)
- Power Supply Unit(s) (Pre-installed)
- System Fans (Pre-installed)
- Server Board (Pre-installed)
- Fan Board (Pre-installed, if supported)
- HDD Backplane (Pre-installed)



1. Some components are already pre-installed. Simply properly connect the relevant cables before or after installation. See the Quick Installation Guide for more details.
2. Refer to the user manual of the server board for instructions on how to install server board components.


3.1 Server Top Covers

Removing the Server Top Covers




1. Before removing the top covers, power off the server and unplug the power cord.
2. The system must be operated with all the chassis top covers installed to ensure proper cooling.

1. Release the mortise lock on the rear top cover of the chassis.
2. Press the cover latch button on the top cover.
3. Push the top cover toward the REAR of the chassis to remove the cover from the locked position.




1. Lower the top rear cover on the chassis, making sure the side latches align with the cutouts. Slide the top rear cover toward the FRONT of the chassis.
2. Secure the top rear cover until it is locked in place.
3. Press down the spring button to confirm the top cover is locked with the chassis.
4. Secure the front cover to the chassis with screws.



3.2 Hard Drive

Removing 2.5" and 3.5" Hard Drive


1. Press the locking lever latch on the drive tray to unlock the retention lever.
2. Rotate the lever out and away from the module bay and pull the hard drive out of the drive tray.



The illustrations shown in this manual are examples only, the actual system may differ slightly.


Installing a 2.5" Hard Drive to the Hard Drive Tray

1. Engage the one side of hard drive into the tray by aligning the side bracket.
2. Carefully push down the other side of the hard drive until it is locked into place.




Front Panel-Installing the HDD assembly

1. Slide the drive tray into the HDD bay until the drive is fully seated.
2. Push in the locking lever to lock the drive tray into place.



Rear Panel-Installing the HDD assembly


1. Slide the drive tray into the HDD bay until the drive is fully seated.
2. Push in the locking lever to lock the drive tray into place.



3.3 System Fan

Replacing the System Fan


1. Align the mounting holes on the fan bar with the fan mount on the replacement fan.
2. Please be aware of the mount location of each fan.
3. Gently place the fan on the fan bar. Make sure the fan is well seated.
4. Connect the end of the fan cable to the fan connector.



3.4 Power Supply

Installing the Power Supply Unit

Carefully slide the PSU all the way into the power supply bay until it clicks into place.





3.5 Add-in Card



1. You can install an add-on card to the chassis only when you have a riser card installed on the server board.
2. Before installing the add-on card, power off the server and unplug the power cord.



Replace Add-in Card

1. Loosen the screws on the riser-card by hand.
2. Lift up the riser-card bracket.
3. Loosen the screws on blanking plate.
4. Slide the blanking plate out.





Installing the Add-in Card

1. Remove the screws and plate.
2. Install the add-in card to the riser-card bracket blanking.
3. Secure the add-in card to the assembly with screws.



4. Secure the assembly to the chassis.
5. Lock the screws.
6. Install the duct bracket over the duct assembly and lock it in place with the chassis.
7. Lock the screws by hand.





Installing the CPU (LGA 4677 Socket)




Unplug all power cables before installing the CPU.


1




2




3




4




5




6




7




8



9



10



Appendix


Installation of Memory Modules (DIMM)




The DIMM only fits in one correct orientation. It will cause permanent damage to the motherboard and the DIMM if you force the DIMM into the slot at incorrect orientation. For more information about DIMM installation, please refer to the User Manual that comes with the server board used.

Type A (Single Clip)


1



2




3




Type B (Two Clips)


1



2




3



Appendix C

Block Diagram (SP2C741D32TM3)



Contact Information

Contact ASRock Rack or want to know more about ASRock Rack, you're welcome to visit ASRock Rack's website at <http://www.asrockrack.com>; or contact the dealer for further information. For technical questions, please submit a support request form at <https://event.asrockrack.com/tsd.asp>

ASRock Rack Incorporation

e-mail: ASRockRack_sales@asrockrack.com

ASRock Rack EUROPE B.V.

Bijsterhuizen 11-11

6546 AR Nijmegen

The Netherlands

Phone: +31-24-345-44-33

ASRock Rack America, Inc.

13848 Magnolia Ave, Chino, CA91710 U.S.A.

Phone: +1-909-590-8308

Fax: +1-909-590-1026